

STATION ONE: Meeting General Requirements

I certify that the _____ solar car team has successfully passed scrutineering station one.

Chief Judge, Station One

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
1-9.	[Rule 5.2.1.1] What material is used for the roll cage tubing? _____	N/A	
1-10.	[Rule 5.2.1.1] The roll cage tubing outside diameter is greater than 1.9 cm [Rule 5.2.1.2] If not, has a waiver been granted this year for the roll cage? _____ <i>[Team must present a copy of the waiver and the Technical Director must sign here be this step can be passed with a waiver]</i>		
Roll Bar			
1-11.	[Rule 5.2.3] The car equipped with a structural frame member that extends at least 5 cm above the driver's head, protecting the driver in the event of a roll over		
1-12.	[Rule 5.2.3.2] What material is used for the roll bar tubing? _____	N/A	
1-13.	[Rule 5.2.3.2] The roll bar tubing outside diameter is at least 5 cm If not, has a waiver been granted this year for the roll bar? _____ <i>[Team must present a copy of the waiver and the Technical Director must sign here be this step can be passed with a waiver]</i>		
1-14.	[Rule 5.2.3.2] The roll bar tubing wall thickness meets the minimum specified in the rules <i>[1.0 mm chromoly steel, 1.5 mm carbon steel, 3.2 mm aluminum]</i> If not, has a waiver been granted this year for the roll bar? _____ <i>[Team must present a copy of the waiver and the Technical Director must sign here be this step can be passed with a waiver]</i>		
1-15.	[Rule 5.2.3.1] Roll bar is welded to frame in no less than two points on each side		
1-16.	[Rule 5.2.3] If driver's head rises above the top of the solar car body, car has additional roll bars to deflect body over the driver in event of a collision		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Crush Zones			
1-17.	[Rule 5.2.2.2(a)] Front and Rear crush zone structures at minimum; provide protection from 35cm to 50cm off the ground throughout the entire width of the driver's compartment		
1-18.	[Rule 5.2.2.2(b)] Left side and right side crush zone structures at minimum; provide protection from 35cm to 50cm off the ground and run from 15cm in front of the driver's feet to 15cm behind the driver's seat		
Vehicle Points			
1-19.	[Rule 5.18] Suspension critical points are lock-nutted, double-nutted, or otherwise secured		
1-20.	[Rule 5.18] Steering critical points are lock-nutted, double-nutted, or otherwise secured		
1-21.	[Rule 5.18] Braking critical points are lock-nutted, double-nutted, or otherwise secured		
1-22.	[Rule 5.18] Drive train critical points are lock-nutted, double-nutted, or otherwise secured		
1-23.	[Rule 5.14] Throttle is free to return to zero when released		
1-24.	[Rule 5.14, 7.5] If the solar car is equipped with cruise control, it has an automatic shut-off when the brake is activated <i>[Solar cars may only be equipped with a cruise control system during closed-track events]</i>		
1-25.	[Rule 5.14] All accelerator mechanisms (manual throttle or cruise control) are directly operated by the driver		
1-26.	[Rule 5.12.1] External signals are visible for 30m		
1-27.	[Rule 5.12.1(b)] Stop lights are DOT approved (and mounted to maximize rear visibility) or visible at 100 meters		
1-28.	[Rule 5.12.1(a)] Stop lights are red in color Turn indicators and hazard lights are amber in color		
1-29.	[Rule 5.13(a)] Seats are equipped with five-point harness system		
1-30.	[Rule 5.13(a)] The harness belts attached securely to a structural component or main frame member of the solar car		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
1-31.	[Rule 5.13(a)] The harness belts are attached with at least 3/8" diameter grade 8 bolts		
1-32.	[Rule 5.18] Seat belt critical points are lock-nutted, double-nutted, or otherwise secured		
1-33.	[Rule 5.12.2] There is a "sound device" or horn that is at least 92 dB readily available to the driver		
1-34.	[Rule 5.12.2] The horn mounted as far forward in the vehicle as possible, facing forward, and outside the driver compartment		
Driver Conditions			
1-35.	[Rule 5.8] The driver's head higher than their feet when in the normal seating position		
1-36.	[Rule 5.9] All drivers driver's eyes are a minimum of 70 cm above ground		
1-37.	[Rule 5.9.1] Forward vision: All drivers can see a point on the ground 8m or less from the front of the car		
1-38.	[Rule 5.9.1] Forward vision: All drivers can see a minimum of 10° from horizon		
1-39.	[Rule 5.9.2] Side vision: From the normal driving position, all drivers can see, without artificial assistance, 90 degrees to either side at all times		
1-40.	[Rule 5.9.3] Rear vision: All drivers can see a vehicle 15 meters directly behind the solar car		
1-41.	[Rule 5.9.3] Rear vision: All drivers can see vehicles 45 degrees in each direction approaching from the rear		
1-42.	[Rule 5.13(d)] Windshield provides protection for the entire face of the driver		
1-43.	[Rule 5.13(g)] Solar car has space for a plastic liquid container for the driver; container cannot roll underneath brake/throttle		
1-44.	[Rule 5.13(h)] Cockpit is equipped with a full belly pan		
1-45.	[Rule 5.13(i)] Forced air ventilation is provided for the solar car's driver		
1-46.	[Rule 5.13(j)] When the driver is seated in the normal driving position, the driver's seat provides back and neck support for the driver		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
1-47.	[Rule 5.13(j)] The driver's seat is attached to main structural frame using at least grade eight bolts 3/8" in diameter		
1-48.	[Rule 5.4.3(f)] Driver's compartment is ventilated separately from the battery area		
1-49.	[Rule 5.13(b)] All sharp objects and frame members within the driver area are padded to help protect the driver		
1-50.	[Rule 5.13(b)] If the car has body shells, shells are securely attached to each other		
1-51.	[Rule 5.13(c)] All vehicle components are secured to the main frame to prevent shifting during impact		
Student Involvement			
1-52.	[Rule 3.8] Is the car obviously constructed by the students? <i>[No "hand-me-down" cars are allowed]</i>		
1-53.	[Rule 3.8] Are the students adequately able to answer judges' questions concerning the principles and operation of the mechanics of the car?		

STATION TWO: Electrical and Battery Requirements

I certify that the _____ solar car team has successfully passed scrutineering station two.

Chief Judge, Station Two

Please do the following:

- (1) Check off all parts of the Electrical and Battery Evaluation Sheet.
- (2) Place non-removable seals on only those batteries carried on that solar vehicle. This prevents teams from switching-out batteries during the race. If teams need additional batteries during the race, they can apply to the Technical Director for new seals.
- (3) Supplemental batteries need not be “sealed” so long as they comply with the provisions set out in Rule 5.4.4.
- (4) Inform the solar teams that the “team judges” will inspect these batteries each morning to ensure that the “sealed” batteries are in place.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Documentation			
2-1.	[Rule 3.6] The team has accurate electrical schematics		
2-2.	[Rule 3.6] The team has accurate solar cell documentation, including list price and cell efficiency		
2-3.	[Rule 3.6] The team has accurate motor and controller documentation		
2-4.	[Rule 3.6] The team has accurate main fuse documentation		
2-5.	[Rule 3.6] The team has accurate disconnect switch documentation		
Propulsion Battery System			
2-6.	[Rule 5.4.3(a)] Propulsion batteries secure from front, rear, and lateral impact		
2-7.	[Rule 5.4.3(b)] Propulsion batteries strapped down or held in place in event of a rollover		
2-8.	[Rule 5.4.3(c)] Inside of propulsion battery box insulated or non-conductive		
2-9.	[Rule 5.4.3(d)] Propulsion battery box not used as dedicated crush zone		
2-10.	[Rule 5.4.3(e), 5.4.3(f)] Propulsion batteries enclosed in a sealed battery box that provides adequate ventilation <i>Note: The battery box does not yet need to be sealed by event officials.</i>		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
2-11.	[Rule 5.4.3(f)] Propulsion battery box fans cycle air within the battery box at least 4 times per minute		
2-12.	[Rule 5.4.3(f)] Propulsion battery box is equipped with a forced air ventilation system that vents to the exterior of the car.		
2-13.	[Rule 5.4.3(g)] Propulsion battery box securely fastened to the vehicle's structure		
2-14.	[Rule 5.7.1, 5.7.2] Connections clear from entanglement and protected		
2-15.	[Rule 5.7.1] All wires connected from the battery to the motor controller and disconnects are properly sized for expected continuous system current		
2-16.	[Rule 5.7.1] Propulsion system connectors are not insulated with electrical tape		
2-17.	[Rule 5.5] Propulsion system isolated from the vehicle frame		
2-18.	[Rule 3.6] Propulsion batteries match documentation submitted by the team		
2-19.	Battery Capacity _____ Number of Batteries _____ Total Battery Capacity _____ [Rule 5.4] Total Battery Capacity is less than 5 kWh		
2-20.	[Rule 5.4] Battery type is appropriate for division		
Motor and Controller Information			
2-21.	Motor Manufacturer: _____ Motor Model: _____ Controller Manufacturer: _____ Controller Model: _____ [Rule 10.1] Motor type allowed in the entered division		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Assistance Devices			
2-22.	<p>[Rule 5.6] I (we) certify that all devices used to assist the start, stop, or powering of the car (umbilical cords, soft start devices, etc.) are carried on the car and are a permanent part of the electrical system.</p> <hr/> Signature of team captain(s)	N/A	
Supplemental Battery System			
2-23.	[Rule 5.4.4] Supplemental batteries totally isolated from the propulsion batteries		
2-24.	<p>[Rule 5.4.4(b)] Driver aggressively warned when supplemental battery voltage is low <i>Note: Advise the team that a supplemental battery should be removed from the car before charging. Teams should never give the appearance that they are charging their main battery pack when they are just charging their supplemental battery.</i></p>		
2-25.	[Rule 5.5] Auxiliary power system isolated from the vehicle frame		
2-26.	[Rule 5.4.4(c)] Supplemental batteries secure from front, rear, and lateral impact		
2-27.	[Rule 5.4.4(c)] Supplemental batteries strapped down or held in place in event of a rollover		
2-28.	[Rule 5.4.4(c)] Supplemental batteries enclosed in a sealed battery box		
2-29.	[Rule 5.5.2] Connections clear from entanglement and protected		
Electrical System Check			
2-30.	[Rule 5.16] High Voltage “points” properly identified and insulated for battery connections (if greater than 36 volts)		
2-31.	[Rule 5.16] High Voltage “points” properly identified and insulated for motor controller (if greater than 36 volts)		
2-32.	[Rule 5.16] High Voltage “points” properly identified and insulated for switches and fuses (if greater than 36 volts)		
2-33.	[Rule 5.16] High Voltage “points” properly identified and insulated for solar cells/panels		
Disconnects			

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
2-34.	[Rule 5.4.5] Internal motor disconnect is accessible to the driver and is properly marked		
2-35.	[Rule 5.4.5] External motor disconnect is accessible to the driver and is properly marked		
2-36.	[Rule 5.4.5(a)] Motor disconnects are push-pull in type		
2-37.	[Rule 5.4.5(b)] Motor disconnects are labeled as "Motor Disconnect" with marked "ON" and "OFF" positions		
2-38.	[Rule 5.4.5(c)] Motor disconnects are rated for the expected voltage and current		
2-39.	[Rule 5.4.5(f)] Motor disconnects are wired in series		
2-40.	[Rule 5.4.5] Internal array disconnect is accessible to the driver and is properly marked		
2-41.	[Rule 5.4.5] External array disconnect is accessible to the driver and is properly marked		
2-42.	[Rule 5.4.5(a)] Array disconnects are push-pull in type		
2-43.	[Rule 5.4.5(b)] Array disconnects are labeled as "Motor Disconnect" with marked "ON" and "OFF" positions		
2-44.	[Rule 5.4.5(c)] Array disconnects are rated for the expected voltage and current		
2-45.	[Rule 5.4.5(b)] Array disconnects are wired in series		
Main Battery Pack Fuse			
2-46.	[Rule 5.4.2(b)] Main fuse is rated as "Fast Blow" or "Very Fast Blow" and for DC voltage		
2-47.	[Rule 5.4.2(c)] Fuse Rating: _____ Peak Current Draw: _____ Main fuse is rated for no more than 125% of the expected current draw		
2-48.	[Rule 5.4.2(d)] Main fuse is placed in an enclosure separate from battery and power tracker enclosures		
2-49.	[Rule 5.4.2(d)] Main fuse is no more than 15 cm from the outside of the battery box		
2-50.	[Rule 5.4.2] Main fuse is directly connected to the positive or negative terminal of the propulsion battery (e.g. no switches in between fuse and terminal)		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Solar Array			
2-51.	[Rule 5.3.3] Solar array has no reflecting devices		
2-52.	[Rule 3.6] Number of cells/modules: _____ Watts per cell/module: _____ W <i>Note: Verify with documentation</i> Computed peak wattage: _____ W	N/A	
2-53.	[Rule 5.3.1] Efficiency of cells/module: _____ % <i>Note: Verify with documentation.</i>	N/A	
2-54.	[Rule 10] Solar cells meet all the requirements for the division that the team intends to compete in.		
2-55.	The cells of the solar car match the documentation that has been submitted to the race _____ Signature of Chief Judge, Station 2 The team acknowledges that the cell documentation submitted is correct and matches what is on the solar car _____ Signature of Team Captain(s)	N/A	
Student Involvement			
2-56.	[Rule 3.8] The students was adequately able to answer judges questions concerning the principles and operation of the electronics of the car		

STATION THREE: Tilt and Turning Radius Checks

I certify that the _____ solar car team has successfully passed scrutineering station three.

Chief Judge, Station Three

Tilt Test:

You will want to ask the team to tilt their vehicle approximately 20 degrees. Teams will lift the solar car along a line perpendicular with the drive axle.

The purpose of this test is to check the following:

- (1) Make sure that the car won't collapse when lateral stresses are applied to the wheels and tires.
- (2) Make sure the vehicle can turn within a safe distance.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Tilt Test			
3-1.	[Rule 5.1.2] The vehicle was able to endure the stresses associated with tilting the car approximately 20 degrees		
3-2.	[Rule 5.1.2] The track (distance between front wheels) is no less than half the wheel base (distance between front and rear wheels)		
Weight Distribution Check [optional]			
3-3.	Weight on Front-Left tire: _____ kg	N/A	
3-4.	Weight on Front-Right tire: _____ kg	N/A	
3-5.	Weight on Rear-Left tire: (Rear for 3 wheeled car) _____ kg	N/A	
3-6.	Weight on Rear-Right tire: (N/A for 3 wheeled car) _____ kg	N/A	
3-7.	Overall Weight: _____ kg	N/A	

Turning Radius Test:

Ask the team to drive their car and make a 180 degree turn. This should be possible within a diameter of 15 meters. The purpose of this test is to ensure that the car will be able to negotiate sharp turns on the road.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Turning Radius Test			
3-8.	[Rule 5.11.1] The vehicle was capable of making a 180 degree turn within a diameter of 15 meters		
3-9.	[Rule 5.11] The vehicle was stable while making the turn		
3-10.	[Rule 5.11] The steering and suspension mechanisms adequately handle the stresses of the turn		

STATION FOUR: Vehicle Handling – Slalom

I certify that the _____ solar car team has successfully passed scrutineering station four.

Chief Judge, Station Four

Slalom Test:

The purpose of this test is to determine whether:

- (1) The vehicle will be able to safely avoid obstacles in the road without the car collapsing under lateral forces.
- (2) The drivers have the necessary skills to negotiate the slalom course.
- (3) Rule 5.2.1 seeks to ensure vehicle stability. Please observe the vehicle for any irregular movements during this part of the scrutineering process.

Slalom Test Preparation:

Set up a slalom course using at least six cones, with 40 feet between each cone. Require the team to navigate between the cones at a reasonable speed that simulates road conditions. Be sure that the course is secure so that parking lot traffic, bystanders, or other solar cars will not interfere with the car being evaluated.

Ask the team to first run the slalom course at a *slow speed* to allow them to become familiar with the course. Then require the team to drive the course at a speed simulating road conditions [approximately 20 mph]. Each driver on a team must demonstrate their ability to successfully drive the course.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Slalom Test			
4-1.	[Rule 7.6] The vehicle was able to endure the stresses associated with quick turns		
4-2.	[Rule 7.6] The vehicle appeared stable during the running of the slalom course		

Inspection Step	Scrutineering Criteria				
4-3.	<p>For each driver, [Rule 5.13(e)] Egress: Driver can egress from the car in 15 seconds without assistance. Everything must be in place prior to egress, including seat belts, water, and fire extinguishers.</p> <p>[Rule 7.6] Slalom: Driver appeared to have the skills necessary to avoid obstacles on the road or track.</p> <p>[Rule 5.2.2.1] Crush Zone: Driver has a minimum of 15 cm of horizontal distance from his or her shoulders, hips, and feet to the inside of the most exterior structural frame member.</p>				
Slalom Test					
Driver Name	Driver License	Egress Pass	Slalom Pass	Crush Zone Pass	Judges Initials

Inspection Step	Scrutineering Criteria				
4-3.	<p>For each driver, [Rule 5.13(e)] Egress: Driver can egress from the car in 15 seconds without assistance. Everything must be in place prior to egress, including seat belts, water, and fire extinguishers.</p> <p>[Rule 7.6] Slalom: Driver appeared to have the skills necessary to avoid obstacles on the road or track.</p> <p>[Rule 5.2.2.1] Crush Zone: Driver has a minimum of 15 cm of horizontal distance from his or her shoulders, hips, and feet to the inside of the most exterior structural frame member.</p>				
Slalom Test					
Driver Name	Driver License	Egress Pass	Slalom Pass	Crush Zone Pass	Judges Initials

STATION FIVE: Braking Tests

I certify that the _____ solar car team has successfully passed scrutineering station five.

Chief Judge, Station Five

Braking Test:

The purpose of this test is to check the following:

- (1) The vehicle will be able to safely stop under real world conditions.
- (2) The drivers have the necessary skills to make these critical stops.
- (3) To ensure that all brake components are in good working order.

Braking Test Preparation:

Set up a braking course using a solar powered speed-sensing device. Clearly mark the starting point, and the point at which the solar cars will be required to apply their brakes.

Conducting the test:

- (1) Physically check brake assembly to ensure that all brake components are in good working order.
- (2) Make sure that your course is clear of obstructions and cross-traffic.
- (3) Explain to the vehicle drivers exactly what is expected of them.
- (4) Physically show them where the “start” line and the “apply-the-brake” line are located.
- (5) Tell them that they have to accelerate to road speeds, and then demonstrate that they can stop within a reasonable amount of time.

<u>Vehicle Speed:</u>	<u>Required stopping time:</u>
Traveling less than 15 mph	N/A (Below qualifying speed)
15 mph	2.0 seconds
20 mph	2.5 seconds
25 mph	3.0 seconds
30 mph	3.5 seconds

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Braking Test			
5-1.	[Rule 5.10] All brake components are in good working order		
5-2.	[Rule 5.10] There are two separate foot pedals that are structurally sound		
5-3.	[Rule 5.10] If two separate foot pedals are linked, each pedal can be independently operated if the linkage fails		
5-4.	[Rule 5.10] With the driver engaging only the primary braking system, the car remains stationary when pushed		
5-5.	[Rule 5.12.1(c)] With the driver engaging only the primary braking system, stop lights are activated		
5-6.	[Rule 5.10] With the driver engaging only the secondary braking system, the car remains stationary when pushed		
5-7.	[Rule 5.12.1(c)] With the driver engaging only the secondary braking system, stop lights are activated		
5-8.	[Rule 5.18] All braking components are properly lock-nutted, double-nutted, or otherwise secured		
5-9.	[Rule 5.10] The vehicle was stable and in control during braking process		
5-10.	[Rule 5.10] The vehicle came to a complete, safe stop within the required amount of time		
5-11.	[Rule 5.10] Braking and steering components were able to handle the stress of braking		

STATION SIX: Endurance Test

I certify that the _____ solar car team has successfully passed scrutineering station six.

Chief Judge, Station Six

Endurance Test:

The purpose of this test is to determine whether the vehicle will be able to safely travel an extended distance, to determine if there is adequate communication between the solar car and the chase vehicle, and to simulate a mechanical failure to demonstrate procedures for safely loading and unloading the solar car.

Preparation for the test:

See that there is a clear path for the vehicles to drive from the scrutineering area to the test area. Make sure that the test area is clear of any other vehicle. Inform the team and chase personnel of the procedures that will be followed in the event that a solar car has a problem during the test.

Procedure:

- (1) Check chase vehicle for requirements as specified below.
- (2) Make sure that the test area is clear of any other vehicle.
- (3) Explain to the solar car driver and the chase vehicle personnel exactly what is expected of them:
 - a. Solar Car: Make at least one complete lap of the test area
 - b. Chase Vehicle: Positioned ready to retrieve the vehicle in the event that a problem occurs
- (4) Have personnel check communications during the test.
- (5) Observe the performance of the solar car and its driver.
- (6) Only one driver needs to put the solar car through the endurance test.
- (7) Have driver complete one full lap at their fastest speed. This counts as the qualifying lap time.
- (8) Full Speed Panic Stop: The driver must safely make a panic stop from full cruising speed
- (9) Have solar car go out into the test area and radio that there has been a mechanical failure. Send trailer to load solar car and observe procedure.
- (10) Have the solar car returned to the scrutineering area and observe unloading procedure.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Solar Car Inspection			
6-1.	[Rule 5.13(k)] Solar car has baking soda for battery spills		
6-2.	[Rule 5.13(f), 7.8] Solar car has fire extinguisher		
6-3.	[Rule 7.8] Solar car has safety vest for driver (track race only)		
Lead Vehicle Inspection			
6-4.	[Rule 19.2.1, 19.2.2.1] Lead Vehicle has flashing amber light (road race only)		
Chase Vehicle Inspection			
6-5.	[Rule 5.13(k)] At least one Chase Vehicle has baking soda for battery spills		
6-6.	[Rule 5.13(f), 7.8] At least one Chase Vehicle has fire extinguisher		
6-7.	[Rule 19.2.1, 19.2.2.1] Each Chase Vehicle has flashing amber light		
6-8.	[Rule 7.8] At least one Chase Vehicle has at least 3 traffic cones or warning triangles		
6-9.	[Rule 19.2.2.1] Each Chase Vehicle has rear Caution Sign attached (road race only)		
6-10.	At least one Chase Vehicle carries proof of liability insurance for solar car		
6-11.	[Rule 5.12.1(e), 19.2.2.8] Each Chase Vehicle has four amber ECCO 3510 or 3518 lights mounted		
Scoring			
6-12.	Driver has required skills to drive endurance course		
6-13.	Solar car able to endure the test		
6-14.	Chase Vehicle personnel have necessary skills		
6-15.	[Rule 5.17] Inter-vehicle communications work properly		
6-16.	Chase Vehicle carries proof of liability insurance		
Full Speed Panic Stop			
6-17.	Car appears stable when performing the panic stop		
6-18.	Car able to come to a complete stop without any mechanical failures		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Designation of Specific Responsibilities [Rule 7.8]			
6-19.	Who is the team designated team member to handle road safety issues? _____	N/A	
6-20.	Who is the team designated team member to handle health issues? _____	N/A	
Radios			
6-21.	Will the team be using FRS or GMRS radios? Yes No If the team is using FRS or GMRS radios, what is the team's preferred channel? _____	N/A	
Trailer Loading and Unloading			
6-22.	Teams, Drivers, and Chase Vehicle Personnel have been thoroughly informed of the procedures that will be followed in the event that a solar car has a problem on the race course.		
6-23.	Solar car was able to be safely loaded onto the trailer		
6-24.	Solar car was able to be safely unloaded from the trailer		

PROCEDURE IF A PROBLEM OCCURS WHILE A SOLAR CAR IS ON THE RACE TRACK:

The tower will indicate to the other teams that a problem has occurred on the track. This will be done by waving a yellow flag. Each team is also required to notify its driver by inter-vehicle radio. Drivers must use extreme caution when passing a vehicle that has pulled off the speedway. Road speeds must be appropriate for the conditions. Excessive speed will be penalized.

Malfunctioning Vehicle:

- (1) The driver will attempt to drive the car off the track. The driver will exit the vehicle, maintain a safe position away from the track, and wait for the chase team. Under no circumstances is the driver to abandon the car.
- (2) If the car can not be driven off the track, the driver will do everything possible to position the car in a safe position. The driver will then exit the vehicle, maintain a safe position away from the track, and wait for the chase team.
- (3) The chase vehicle will slowly move on the track and drive to the solar car. [Yellow lights flashing!]
 - a. Minor repairs can be made on the track so long as the solar car is safely away from the flow of traffic.
 - b. Major repairs require that the car be transported to the garage area.
- (4) All flow of traffic (solar cars and chase vehicles) will be in the direction of the solar cars. No chase vehicle will attempt to drive against the flow of "traffic." Chase vehicles must yield to any approaching solar car.
- (5) Any violation of these rules will produce major penalties.

A green flag will be waved to indicate that the race course is clear. Teams will also notify their drivers by inter-vehicle communication. Normal speeds can now be resumed.

STATION SEVEN :

Road Test

(On Road Events Only)

I certify that the _____ solar car team has successfully passed scrutineering station seven.

Chief Judge, Station Seven

Road Test:

The purpose of this test is to determine whether the vehicle will be able to safely travel on undivided highways with on-coming traffic. This test is not applicable for closed track events.

Preparation for the test:

See that there is a clear path for the vehicles to drive from the scrutineering area to the test area. Make sure that the test area is clear of any traffic. Check to make sure the solar car has passed stations all other station prior to attempting this station.

Procedure:

- (1) Make sure the solar car has passed all other stations.
- (2) Make sure that the test area is clear of any traffic.
- (3) Position the solar car and test truck on opposite sides of the test area facing each other.
- (4) Explain to the solar car driver and the test truck driver exactly what is expected of them:
 - a. Solar Car: Accelerate the solar car to road speeds and pass the test truck on the right side.
 - b. Test Truck: Accelerate the truck to normal road speeds and pass the solar car on the right side.
- (5) Observe the stability of the solar car.
- (6) Only one driver needs to put the solar car through the road test.

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Road Test			
7-1.	The vehicle was able to endure the stresses associated with the vortices created by the passing truck		
7-2.	The vehicle appeared stable during the running of the road test		

STATION EIGHT: Electric-Solar Powered Vehicle Station

I certify that the _____ electric-solar powered car has successfully passed scrutineering station eight.

Chief Judge, Station Eight

Concept:

The Electric-Solar Powered Car Division is designed to simulate a “real world” solar application. The solar car itself will be a two passenger vehicle that could easily run in a neighborhood environment. The Solar Power Charging Station simulates a permanent (or mobile) facility that would be used to charge the vehicle at home or at work.

Preparation for the test:

Electric-Solar Powered Car Team will travel to the Charging Station Area to conduct Station Eight qualifying.

Procedure:

- (1) Check that the E-SP vehicle for requirements as specified below.
- (2) Explain to the E-SP car driver and passenger what is expected of them:
 - a. Demonstrate the battery box has a maximum of 2 Kw/hr
 - b. Demonstrate that the team has a system for measuring driver/passenger weight and preparing accurate ballast.
 - c. Demonstrate that the battery box can be safely installed
 - d. Demonstrate that the battery box can be safely removed
 - e. Demonstrate that the battery box is ventilated both in the E-SP car and at the Power Station.
 - f. Demonstrate that the Power Station is structurally secure
 - g. Demonstrate that the Power Station array can be safely rotated, if the team is tracking the movement of the sun.
- (3) Observe the performance of the E-SP car, driver, and passenger.
- (4) Can both the driver and passenger meet the 15-second emergency egress?

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Physical Regulations			
8-1.	[Rule 32.2.1] The electric-solar powered [E-SP] car has passed all other stations.		
8-2.	[Rule 32.2.2] E-SP car meets minimum dimensions: 4.5m x 1.5m x 1.5m (2015 E-SP cars may have minimum length of 4m)		
8-3.	[Rule 32.2.3(a)] E-SP car has two passengers seated side-by-side		
8-4.	[Rule 32.2.3(a)] E-SP car passengers seated upright		
8-5.	[Rule 32.2.4] Team has scale to measure the weight of the drivers		
8-6.	[Rule 32.2.4] Team has adequate ballast to bring driver weight to 320 lbs		
8-7.	[Rule 32.2.6] Team has two separate battery boxes		
8-8.	[Rule 32.2.6(a)] Team demonstrated that each battery box has maximum of 2 kWh		
8-9.	[Rule 32.2.6(b)] Battery box is rigid and easily installed and removed		
8-10.	[Rule 32.2.6(c)] Team demonstrated that battery box can be safely installed and removed		
8-11.	[Rule 32.2.6(b), 5.4.3(f)] Battery box is ventilated in the E-SP car		
8-12.	[Rule 32.2.6(b), 5.4.3(f)] Battery box is ventilated at the Power Station		
Power Station			
8-13.	[Rule 32.3.1] E-SP Charging Station array meet maximum dimensions of 5m x 1.8m		
8-14.	[Rule 32.3.1] E-SP Charging Station array has solar cells with maximum efficiency of 19% or less		
8-15.	[Rule 32.3.2] If the team plans to rotate its solar panel, they demonstrated that this can be done safely		
8-16.	[Rule 32.3.3] Team demonstrated that the power station is stable during large gusts of air		
Power Station Maintenance & Supervision			
8-17.	[Rule 32.4] Team has a definite battery box exchange procedure		

Inspection Step	Scrutineering Criteria	Pass	Judges Initials
Safety Issues			
8-18.	[Rule 5.13(e)] E-SP driver and passenger meet the 15 second safety egress		

Driver Name	Weight (lbs)	Passenger Name	Weight (lbs)	Egress Pass	Judges Initials

Example Discrepancy Sheet

Inspection Step: _____	Write Up	Judges Initials
Issue Description	<p><i>Here is where the judge would explicitly state what the team needs to do to pass the step.</i></p> <p>E.G. <i>The two nuts on the rack unit should be secured with Loctite or by other means and the loose nut on the steering wheel needs to be tightened.</i></p>	
Disposition	<p><i>Here is where we would write down what the team did to fix the problem or denote a failure to comply penalty or other as needed.</i></p> <p>E.G. <i>Rack unit nuts were secured by double-nut. Loose nut on steering wheel was tightened.</i></p>	

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Inspection Step: _____	Write Up	Judges Initials
Issue Description		
Disposition		

Judges Comments for Director Review

Comments:

We certify that the _____ solar car team has successfully passed all scrutineering stations and have adequately demonstrated their ability to compete in the Solar Car Challenge. In addition, we certify that the team has demonstrated a sufficient understanding of their solar car's components.

Race Director

Technical Director

Post Race Inspection

Comments:

We certify that the _____ solar car is compliant with all the regulations of this race.

Date: _____

Time: _____

Race Director

Technical Director